

Franklin International

MATERIAL SAFETY DATA SHEET

MSDS Name: Titebond Solvent Free Fast Grab FRP Adhesive
MSDS Number: 4054
Revision Date: 3/13/01

SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: Titebond Solvent Free Fast Grab FRP Adhesive

CAS Number: none

HMIS Hazard Rating: Health: 1 Fire: 1 Reactivity: 0

Company Identification: Franklin International
2020 Bruck Street
Columbus OH 43207

Contact: Franklin Technical Services
Telephone/Fax: (800) 877-4583 (614) 445-1493
Emergency Phone (24 Hour): Franklin Security
(614) 445-1300
Chemtrec (24 Hour): (800) 424-9300
Chemtrec International: (703) 527-3887

Product Class: Solvent Free adhesive
Product Use: FRP adhesive
Product Code: 3432

Division: Construction Adhesives & Sealants

SECTION 2 - COMPOSITION AND INFORMATION ON INGREDIENTS

Hazardous Ingredients	CAS Number	Percent
Product contains no hazardous ingredients or they are below reportable levels.		

OSHA PELs & ACGIH TLVs are listed in Section 8 where applicable.

SECTION 3 - HAZARD IDENTIFICATION

EMERGENCY OVERVIEW:

Light brown colored mastic. Slippery in the wet state. Do not ingest. Avoid prolonged exposure to skin or vapors. KEEP OUT OF REACH OF CHILDREN.

ROUTES OF ENTRY:

Ingestion: Yes
Inhalation: Yes
Skin: Yes
Eye: Yes

INHALATION:

May be irritating to upper respiratory tract.

INGESTION:

Ingestion is not a probable route of exposure. Harmful if swallowed.

SKIN:

Prolonged or repeated skin contact can cause irritation.

EYE:

Mildly irritating to eyes.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:

Under conditions of normal use chronic affects are not expected.
Possible aggravation of pre-existing skin conditions.

CARCINOGENICITY:

IARC: No

NTP: No

OSHA: No

REPRODUCTIVE TOXICITY:

This product has not been evaluated for reproductive toxicity.

TARGET ORGANS:

Eyes and skin.

SECTION 4 - FIRST AID MEASURES

INHALATION:

Remove to fresh air. If difficulty persists, seek medical attention.

INGESTION:

Call poison control center immediately. Follow their specific instructions. Do not induce vomiting.

SKIN:

Wash with soap and water. Contact a physician if irritation develops or persists.

EYE:

Hold eyelids apart and flush with plenty of water for at least 15 minutes. Seek medical attention.

SECTION 5 - FIRE-FIGHTING MEASURES

Flammability Class (OSHA) IIIIB

Flash Point: > 200.øF

Setaflash

Explosive Range: Not applicable

EXTINGUISHING MEDIA:

Use alcohol foam, carbon dioxide, water spray, or ABC dry chemical when fighting fires involving this product.

HAZARDOUS COMBUSTION PRODUCTS:

Oxides of carbon may be released during combustion.

FIRE FIGHTING PROCEDURES:

Wear a NIOSH approved self-contained breathing apparatus.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

CONTAINMENT TECHNIQUES:

Use inert absorbent to dike the spill. Keep away from drains.

CLEAN-UP:

Spread absorbent over material and scrape up material/absorbent and place in an approved container. If product has dried scrape up and place in an approved container.

EMERGENCY MEASURES:

Isolate hazard area. Keep unnecessary and unprotected personnel from entering area. Wear all appropriate personal protection equipment (PPE) (see Section 8).

SECTION 7 - HANDLING AND STORAGE

HANDLING:

Wash thoroughly after handling.

Avoid prolonged or repeated contact with the skin.

STORAGE:

Keep from freezing.

PRECAUTIONARY STATEMENT:

Keep out of the reach of children.

SECTION 8 - EXPOSURE CONTROLS AND PERSONAL PROTECTION

Occupational Exposure Limits

ACGIH TLV	ACGIH TLV-C	ACGIH STEL	OSHA STEL	OSHA PEL
-----------	-------------	------------	-----------	----------

ENGINEERING CONTROLS:

Use local exhaust as needed to maintain occupational exposure limits.

OTHER:

Facilities storing or utilizing any chemical should be equipped with an eyewash facility and a safety shower.

RESPIRATORY PROTECTION:

Respiratory protection is not expected to be necessary under normal use. Follow requirements for respiratory protection in OSHA 1910.134.

EYE PROTECTION:

Chemical splash goggles (ANSI Z87.1 or approved equivalent).

SKIN PROTECTION:

Where skin contact can occur, wear impervious gloves.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Form:	Mastic
Appearance/Color:	Light brown
Odor:	Mild
Solubility (in water):	Miscible
pH Value:	5.
Boiling Range/Point:	212.0F
Evaporation Rate:	Slower than n-Butyl Acetate

% Volatile:	33.%
Specific Gravity:	1.41
VOC:	2.6 g/l

SECTION 10 - STABILITY AND REACTIVITY

Stability:	This product is stable
Hazardous Polymerization:	Hazardous polymerization will not occur

CONDITIONS TO AVOID:

Strong acids and strong bases

INCOMPATIBILITY:

Easily oxidizable materials.

SECTION 11 - TOXICOLOGICAL INFORMATION

This formulation has a low order of acute and chronic toxicity by all routes of exposure. Prolonged or repeated exposure may cause skin irritation. Direct contact may cause eye irritation.

Exposure to any chemical substance, including those with a low order of toxicity, should be controlled and minimized to avoid harmful effects.

SECTION 12 - ECOLOGICAL INFORMATION

This formulation has not been tested for environmental effects.

SECTION 13 - DISPOSAL CONSIDERATIONS

WASTE DISPOSAL:

Disposal of this product must comply with all applicable federal, state and local regulations.

CONTAINER DISPOSAL:

Disposal of this container should comply with all applicable federal, state and local regulations.

SECTION 14 - TRANSPORT INFORMATION

UN Number	none
UN Pack Group	N/A
UN Class	Nonhaz
ICAO/IATA Class	Nonhazardous
IMDG Class	Nonhazardous
Shipping Name	Nonhazardous

Packaging may not be approved for shipping by air. Please contact Franklin International for further information.

SECTION 15 - REGULATORY INFORMATION**TSCA (Toxic Substances Control Act Inventory):**

All components of this product are listed on the TSCA inventory except as exempted.

PENNSYLVANIA:

Hazardous components required to be listed at 1% or more:

calcium carbonate; limestone; 1317-65-3

kaolin clay; kaolin; 1332-58-7

Non-hazardous components required to be listed at 3% or more:

urea 57-13-6; dipropylene glycol dibenzoate 27138-31-4; polyvinyl

acetate emulsion 24980-61-8; water 7732-18-5

NEW JERSEY:

polyvinyl acetate emulsion 24980-61-8; water 7732-18-5; clay

1332-58-7; calcium carbonate 1317-65-3; dipropylene glycol dibenzoate

27138-31-4

SECTION 16 - OTHER INFORMATION**DISCLAIMER:**

While the information and recommendations set forth herein are believed to be accurate as of the data hereof, Franklin International makes no warranty, express or implied, with respect thereto and disclaims all liability from reliance thereon.